

# The Effectiveness of Urban Forest in Absorbing CO2 Emission at Rajekwesi Type A Terminal

*by Oktavianus Cahya Anggara .*

---

**Submission date:** 27-Aug-2021 01:08PM (UTC+0700)

**Submission ID:** 1636685858

**File name:** 33701-115802-1-PB.pdf (222.01K)

**Word count:** 4339

**Character count:** 21374

# The Effectiveness of Urban Forest in Absorbing CO<sub>2</sub> Emission at Rajekwesi Type A Terminal

Oktavianus Cahya Anggara<sup>1</sup>, and Laily Agustina Rahmawati<sup>1</sup>

<sup>1</sup>Program Studi Ilmu Lingkungan, Fakultas Sains dan Teknik, Universitas Bojonegoro; e-mail: [oktavianuscahya@gmail.com](mailto:oktavianuscahya@gmail.com)

## ABSTRACT

The terminal in Bojonegoro District is Rajekwesi Type A Terminal. It is located close to the CBD that has resulted in a decrease in environmental quality, due to gas emissions released by motor vehicles. The decrease in environmental quality can be overcome with an ecological approach, for example by creating or expanding green open spaces (urban forest). This study aimed to provide information about the capability of urban forest of the terminal to absorb CO<sub>2</sub> emissions. This study began with a survey counting the number of motor vehicles at the gateway of the terminal on Sunday, Monday, Wednesday, Friday and Saturday for 24 hours. Then, the measurement of tree biomass was carried out using the nondestructive method. After the data was collected, the amount of CO<sub>2</sub> emissions from motor vehicles was calculated by adding up CO<sub>2</sub> emissions in a stationary (idle) position when it was moving. The total CO<sub>2</sub> emissions of motor vehicles at Rajekwesi Type A Terminal was 292.058,087 kgCO<sub>2</sub>/year. The amount of carbon sink (Wtc) of a tree was calculated by multiplying the total biomass (Wt) by the carbon concentration. The amount of Wtc at the urban forest of Rajekwesi Type A Terminal was 4.366,059 kg/year. After the amount of Wtc was found out, the amount of CO<sub>2</sub> absorbed by the tree could be found out by multiplying Wtc by the conversion constant of the carbon (C) element to CO<sub>2</sub> (3,67). The amount of CO<sub>2</sub> absorbed by the trees at the urban forest of Rajekwesi Type A Terminal was 16.023,44 kgCO<sub>2</sub>/year. If they were compared, the absorption of CO<sub>2</sub> was still much smaller than the emission rate. Thus, the function of the urban forest of terminal as an absorber of CO<sub>2</sub> emissions was still not optimal.

**Keywords:** Urban forest, CO<sub>2</sub> emissions, Terminals, Motor vehicles, Trees

**Citation:** Anggara, O. C., and Rahmawati, L. A. (2021). The Effectiveness of Urban Forest in Absorbing CO<sub>2</sub> Emission at Rajekwesi Type A Terminal. *Jurnal Ilmu Lingkungan*, 19(1), 60-65, doi:10.14710/jil.19.1.60-65

## 1. Introduction

When viewed from the regional transportation network, Bojonegoro District is a crossing area for transportation from various areas, such as Tuban District, Lamongan District, Nganjuk District, Madiun District, Ngawi District and Blora District. This position is also supported by the region's potential as an agricultural, tourism and mining area. Therefore, what needs attention is the transportation network, especially land transportation facilities and terminals, so that it can support all the activities of its districts.

The terminal in Bojonegoro District is Rajekwesi Type A Terminal. As the node of the transportation network, the terminal is a major source of air pollution. The location of the terminal, which is close to office, trade, services, education and health sites, has caused environmental degradation in the surrounding area, due to gas emissions released by motor vehicles. Based on *Informasi Kinerja Pengelolaan Lingkungan Hidup Daerah (IKPLHD) Provinsi Jawa Timur* in 2016, fuel use from the transportation sector in 2016 was dominated by gasoline, amounting to 14,46 million kiloliters, and diesel, amounting to 6.723,01 kiloliters. By using the IPCC GL 2006 method, from the 2016 fuel use, the greenhouse gas emission was 33.891,51 Gg CO<sub>2</sub>e.

60

The environmental quality degradation can be overcome with an ecological approach. The ecological approach emphasizes the relationship between humans and their environmental activities, so that humans and their various activities continue to be the focus in relation to their abiotic, biotic, social, economic and cultural environments. An example of the effort to overcome environmental degradation, with an ecological approach, is the creation or expansion of urban forests. Urban forest is a form of green open space, which is useful for controlling the microclimate. It serves to absorb solar radiation, lower air temperature, increase air humidity, reduce wind speed and absorb pollutants from transportation activities (Fandeli et al., 2004; Hamdaningsih et al., 2010).

Based on the identification of the problem, this study aims to provide information on the capacity of urban forest to absorb CO<sub>2</sub> emissions at the terminal. The scope of the area in this study is Rajekwesi Type A Terminal, which is located on Veteran Street, Sukorejo Village, Bojonegoro District. For the scope of the material, the measurement of CO<sub>2</sub> levels was limited to the calculation of CO<sub>2</sub> emissions from motor vehicles. This measurement was a measurement of node I (observations made on emission sources),

which may produce more accurate pollutant data, because it is directly related to the intensity of the emitter's activities (Soedomo, 2001; Kosegeran et al., 2013). Meanwhile, biomass measurements were only carried out on trees. Measurements of understory biomass were not carried out because of their very low absorption of CO<sub>2</sub>. According to Birdsey (1992) and Boyce (1995), the percentage of carbon content in each tree stand was around 30,6 %, while in understory it was around 1,5 % (Fandeli et al., 2004; Hairiah and Rahayu, 2007; Ludang et al., 2017).

## 2. Research Methods

### 2.1. Data Collection Method

Data collection in this study was carried out through a survey of counting the number of motor vehicles and a survey of tree biomass measurements. The survey to count the number of motor vehicles was conducted on Sunday, Monday, Wednesday, Friday and Saturday, for 24 hours, with 15 minute intervals. This survey was conducted at the terminal entrance by counting the number of motor vehicles entering the terminal.

For the survey, the measurement of tree biomass was carried out by means of nondestructive technique (not cutting down trees) (Hairiah and Rahayu, 2007; Ihsan et al., 2015), by recording the names, ages and diameter of the trunk at breast height (1,3 m from the ground) of all trees. Consequently, the specific gravity (SG) of wood from each tree species was calculated by cutting the wood from one of the branches, then by measuring its length and diameter. The wood samples were put in an oven at 100°C for 48 hours and then weighed for their dry weights. The wood SG could be calculated by dividing its dry weight by its volume.

### 2.2. Data Analysis Method

Data analysis in this study included the analysis of calculating CO<sub>2</sub> emissions and the analysis of calculating the carbon sink in trees. The CO<sub>2</sub> emission of each type of motor vehicle can be obtained by adding up the CO<sub>2</sub> emission of a motor vehicle when it was in a stationary (idle) position and when it moved, based on the following equations.

$$ECO_2 = t_{stationary} \times cons_{fuel} \times conv_{fuel}$$

where:

ECO<sub>2</sub>(s) : CO<sub>2</sub> emission of motor vehicle in stationary position (kgCO<sub>2</sub>)  
 tstationary : duration of the vehicle engine run in stationary position (minutes)  
 confuel : total fuel consumption at stationary position per minute (l/minute)  
 convfuel : fuel conversion factor to CO<sub>2</sub> (kgCO<sub>2</sub>/l)

$$ECO_2(g) = l_{travel} \times conv_{fuel}$$

where:

ECO<sub>2</sub>(g) : motor vehicle CO<sub>2</sub> emissions when moving (kgCO<sub>2</sub>)  
 ltravel : the distance traveled by a motor vehicle while at the terminal (km)  
 convfuel : fuel conversion factor to CO<sub>2</sub> (kgCO<sub>2</sub>/km)

First, the amount of CO<sub>2</sub> emission for each type of motor vehicle was calculated; then it was multiplied by the number of units for each type of motor vehicle in the terminal on Sunday, Monday, Wednesday, Friday and Saturday. Next, it was averaged for each day's character, so that the average daily CO<sub>2</sub> emissions were obtained. Finally, it was multiplied by 365 to find the total annual CO<sub>2</sub> emission.

The analysis of the carbon sink in trees was preceded by the processing of biomass data. The method of processing tree biomass data (Hairiah and Rahayu, 2007; Ihsan et al., 2015) is to use allometric equations that have been developed by previous researchers, whose measurements begin with felling and weighing several trees.

$$Y = 0,11p d^{2,62}$$

where:

Y : tree mass (kg/tree)  
 d : stem diameter at breast height/ dbh (cm)  
 p : wood SG (g/cm<sup>3</sup>)

Then, the tree biomass was divided by the age of the tree to obtain the tree biomass per year. The total biomass of all trees at the terminal were added up, whether they were small, medium or large, to obtain the total tree biomass (Wt).

The carbon concentration in biomass was about 46 %. Therefore, the estimated amount of carbon sink (Wtc) can be calculated by multiplying the total tree biomass (Wt) by the carbon concentration (Hairiah and Rahayu, 2007; Fitriada et al., 2020). After the amount of carbon sink (Wtc) was known, the amount of CO<sub>2</sub> absorbed by trees could be calculated by multiplying the amount of carbon sink by the constant for the conversion from carbon (C) to CO<sub>2</sub> (3,67) (Fandeli and Muhammad, 2009; Anonymous, 2012).

## 3. Results and Discussion

### 3.1. Motor Vehicles and CO<sub>2</sub> Emissions at Rajekwesi Type A Terminal

The routes and mileages of motor vehicles at Rajekwesi Type A Terminal were different. The closer the distance a motor vehicle traveled, the less was its CO<sub>2</sub> emissions. Conversely, the farther the distance it traveled, the more was its CO<sub>2</sub> emissions. The routes and mileages of motor vehicles at Rajekwesi Type A Terminal can be seen in Table 1.

**Table 1.** Types, Routes and Mileages of Motor Vehicles at Rajekwesi Type A Terminal

No.	Motor Vehicle Type	Routes Taken within the Terminal	Distance Travelled (km)
1.	Motorcycle (small, medium, big)	Entrance gate – private vehicle parking lot – exit	0,213
2.	Sedan/ jeep	Entrance gate – private vehicle parking lot – exit	0,213
3.	Family car/ MPV	Entrance gate – private vehicle parking lot – exit	0,213
4.	Pick-up	Entrance gate – private vehicle parking lot – exit	0,213
5.	Microbus	Entrance gate – rural transport arrival route – rural transport vehicle waiting area – rural transport departure route – exit	0,297
6.	Bus	Entrance gate – inter province/ within province transport arrival route – inter province/ within province transport vehicle waiting area – inter province/ within province transport departure route – exit	0,442

Source: Primary survey, 2020

In addition to the distance traveled, the amount of CO<sub>2</sub> emissions released by motor vehicles was also influenced by the number of motor vehicles (Saadah, 2002; Tim Penulis Pedoman Penyelenggaraan Inventarisasi GRK Nasional, 2012). The highest number of motor vehicles occurred on Friday (a normal day before the weekend). On Fridays, the

number of prospective passengers, especially workers, was higher compared to those of other days, and thus the number of private vehicles used and public vehicles operated were also greater. The number 6 motor vehicles in Rajekwesi Type A Terminal can be seen in Table 2.

**Table 2.** Number of Motor Vehicles at Rajekwesi Type A Terminal

Day	Motorcycle			Sedan/ Jeep (unit)	Family Car/ MPV (unit)	Pick-up (unit)	Microbus (unit)	Bus (unit)	Total (unit)
	Small (unit)	Medium (unit)	Big (unit)						
Sunday	0	474	20	8	17	5	14	114	652
Monday	2	731	61	10	26	8	12	133	983
Wednesday	1	806	93	8	23	7	14	135	1.087
Friday	4	909	69	5	27	6	14	135	1.169
Saturday	1	717	50	7	11	9	16	136	947

Source: Primary survey, 2020

The amount of CO<sub>2</sub> emissions contained in the Rajekwesi Type A Terminal can be calculated by adding up the CO<sub>2</sub> emissions of each type of motor vehicle in stationary (idle) and moving positions. The

CO<sub>2</sub> emissions of each type of motor vehicle in stationary (idle) position can be seen in Table 3, while the CO<sub>2</sub> emissions of each type of motor vehicle in moving position can be seen in Table 4.

**Table 3.** CO<sub>2</sub> Emission for Each Type of Motor Vehicle in Stationary (Idle) Position

No.	Motor Vehicle Type	Running Machine Duration in Stationary Position (minute)	Fuel Consumption in Stationary/ Idle Position* (l/minute)	Conversion Factor Oil Fuel to CO <sub>2</sub> ** (kgCO <sub>2</sub> /l)	CO <sub>2</sub> Emission of Motor Vehicle in Stationary Position (kgCO <sub>2</sub> )
1.	Motor cycle	Small 0,1	0,014	2,10	0,003
		Medium 0,1	0,017	2,10	0,004
		Big 0,1	0,024	2,10	0,005
2.	Sedan/ jeep	0,1	0,127	2,10	0,027
3.	Family car/ MPV	0,1	0,148	2,10	0,031
4.	Pick-up	0,2	0,083	2,58	0,043
5.	Microbus	10,0	0,105	2,58	2,709
6.	Bus	15,0	0,144	2,58	5,573

Source: Primary survey and analysis results, 2020

\* Anonymous, 2012

\*\* Tim Penulis Pedoman Penyelenggaraan Inventarisasi GRK Nasional, 2012

**Table 4.** CO<sub>2</sub> Emission of Each Type of Motor Vehicle When Moving

No.	Motor Vehicle Type	Mileage Average (km)	Conversion Factor Oil Fuel to CO <sub>2</sub> ** (kgCO <sub>2</sub> /km)	CO <sub>2</sub> Emission of Motor Vehicle in Moving Position (kgCO <sub>2</sub> )
1.	Motor cycle	Small 0,213	0,08	0,017
		Medium 0,213	0,10	0,021
		Big 0,213	0,14	0,030
2.	Sedan/ jeep	0,213	0,18	0,020
3.	Family car/ MPV	0,213	0,21	0,023
4.	Pick-up	0,213	0,15	0,017
5.	Microbus	0,297	0,19	0,014
6.	Bus	0,442	0,26	0,031

Source: Primary survey and analysis results, 2020

\*\* Tim Penulis Pedoman Penyelenggaraan Inventarisasi GRK Nasional, 2012

To find out the amount of CO<sub>2</sub> emission for each type of motor vehicle, the CO<sub>2</sub> emissions of motor vehicles in stationary position and moving position were added up. The amount of CO<sub>2</sub> emission for each type of motor vehicle can be seen in Table 5. Based on Table 5, it can be seen that the CO<sub>2</sub> emission of each type of motor vehicle (except motorcycle) was

dominated by CO<sub>2</sub> emission in stationary position. This happens because the amount of fuel that a vehicle burns in a stationary position is greater than the fuel it spends when it moves. The more fuel is burned, the more CO<sub>2</sub> emission is released. The stationary position occurs when the vehicle is loading and unloading passengers and goods.

**Table 5.** CO<sub>2</sub> Emission of Each Type of Motor Vehicle at Rajekwesi Type A Terminal

No.	Motor Vehicle Type	CO <sub>2</sub> Emission of Motor Vehicle in Stationary/ Idle Position (kgCO <sub>2</sub> )	CO <sub>2</sub> Emission of Motor Vehicle in Moving Position (kgCO <sub>2</sub> )	CO <sub>2</sub> Emission of Motor Vehicle (kgCO <sub>2</sub> )
1.	Small	0,003	0,017	0,020
	Medium	0,004	0,021	0,025
	Big	0,005	0,030	0,035
2.	Sedan/ jeep	0,027	0,020	0,047
3.	Family car/ MPV	0,031	0,023	0,054
4.	Pick-up	0,043	0,017	0,060
5.	Microbus	2,709	0,014	2,723
6.	Bus	5,573	0,031	5,604

Source: Analysis results, 2020

After obtaining the amount of CO<sub>2</sub> emissions for each type of motor vehicle, the CO<sub>2</sub> emissions of motor vehicles in the Rajekwesi Type A Terminal are obtained by multiplying the amount of CO<sub>2</sub> emissions

by the number of units for each type of motor vehicle. The CO<sub>2</sub> emissions of motor vehicles at Rajekwesi Type A Terminal can be seen in table 6.

**Table 6.** Total Motor Vehicle CO<sub>2</sub> Emissions at Rajekwesi Type A Terminal

Day	Small (kgCO <sub>2</sub> )	Medium (kgCO <sub>2</sub> )	Big (kgCO <sub>2</sub> )	Sedan/ Jeep (kgCO <sub>2</sub> )	Family Car/ MPV (kgCO <sub>2</sub> )	Pick-up (kgCO <sub>2</sub> )	Mikrobus (kgCO <sub>2</sub> )	Bus (kgCO <sub>2</sub> )	Total (kgCO <sub>2</sub> )
Sunday	0,000	11,850	0,700	0,376	0,918	0,300	38,122	638,856	691,122
Monday	0,040	18,275	2,135	0,470	1,404	0,480	32,676	745,332	800,812
Wednesday	0,020	20,150	3,255	0,376	1,242	0,420	38,122	756,540	820,125
Friday	0,080	22,725	2,415	0,235	1,458	0,360	38,122	756,540	821,935
Saturday	0,020	17,925	1,750	0,329	0,594	0,540	43,568	762,144	826,870
Daily CO <sub>2</sub> emission (kgCO <sub>2</sub> /day)									800,159
Yearly CO <sub>2</sub> emission(kg CO <sub>2</sub> /year)									292.058,087

Source: Analysis results, 2020

### 3.2. Biomass and Carbon Sink in Rajekwesi Type A Terminal

The urban forest in Rajekwesi Type A Terminal was in the form of an area of 0,5 ha. Based on the growth rate, the trees in the urban forest at Rajekwesi Type A Terminal included:

- Small trees/ seedling (dbh 5 - 20 cm)
  - Tanjung (*Mimusops elengi*) : 250 trees
  - Mahogany (*Swietenia mahagoni*) : 71 trees
  - Trembesi (*Samanea saman*) : 2 trees
  - Glodokan (*Polyalthia longifolia*) : 102 trees
  - Sawo kecil (*Manilkara kauki*) : 95 trees
  - Kiarapayung (*Felicium decipiens*) : 1 tree
  - Jackfruit (*Artocarpus heterophyllus*) : 2 trees
  - Mango (*Mangifera indica*) : 1 tree
  - Bintaro (*Cerbera manghas*) : 1 tree
- Medium sized trees/ poles (dbh 20 - 35 cm)
  - Tanjung (*Mimusops elengi*) : 3 trees
  - Mahogany (*Swietenia mahagoni*) : 25 trees
  - Trembesi (*Samanea saman*) : 2 trees
  - Sengon (*Albizia chinensis*) : 2 trees
  - Glodokan (*Polyalthia longifolia*) : 10 trees
  - Sawo kecil (*Manilkara kauki*) : 2 trees
- Large trees / trees (dbh > 35 cm)
  - Mahogany (*Swietenia mahagoni*) : 1 tree
  - Trembesi (*Samanea saman*) : 8 trees
  - Sengon (*Albizia chinensis*) : 2 trees

- Acacia (*Acacia pycnantha*) : 1 tree

Note: dbh (diameter at breast height)

The specific gravity of tree wood/ timber found in the urban forest at Rajekwesi Type A Terminal can be seen in Table 7, while the tree biomass in the urban forest at Rajekwesi Type A Terminal can be seen in Table 8.

The carbon concentration in biomass was around 46 %. Therefore, the estimated amount of carbon sink (Wtc) contained in the urban forest of Rajekwesi Type A Terminal could be calculated by multiplying the total biomass (Wt) in the urban forest at Rajekwesi Type A Terminal by its carbon concentration (Hairiah and Rahayu, 2007; Fitriada et al. al., 2020).

$$Wtc = Wt \times 0,46$$

$$Wtc = 9.491,430 \times 0,46$$

$$Wtc = 4.366,059 \text{ kg/year}$$

where:

Wtc : amount of carbon sink (kg/year)

Wt : total biomass (kg/year)

0,46 : carbon concentration in organic matter

After the amount of carbon sink (Wtc) was known, the amount of CO<sub>2</sub> absorbed by trees in the urban forest at Rajekwesi Type A Terminal could be calculated through the following equation (Fandeli and Muhammad, 2009; Anonymous, 2012):

$$WCO_2 = Wtc \times 3,67$$

$$WCO_2 = 4.366,059 \times 3,67$$

$$WCO_2 = 16.023,44 \text{ kgCO}_2/\text{year}$$

where:

$WCO_2$  : the amount of  $CO_2$  absorbed by trees  
( $kgCO_2/\text{year}$ )

$Wtc$  : amount of carbon sink ( $kg/\text{year}$ )

3,67 : conversion constant of the carbon (C)  
element to  $CO_2$

**Table 7.** Timber Specific Gravity ( $\rho$ ) of the Trees in the Urban Forest at Rajekwesi Type A Terminal

No.	Tree Name		Monocot/ Dicot	Wood Sample			Timber Specific gravity/ $\rho$ ( $g/cm^3$ )
	Local Name	Botanical name		Diameter (cm)	Length (cm)	Dry Weight (g)	
1.	Tanjung	<i>Mimusops elengi</i>	Dicot	1,94	20	47,86	0,81
2.	Mahogany	<i>Swietenia mahagoni</i>	Dicot	1,52	20	23,21	0,64
3.	Trembesi	<i>Samanea saman</i>	Dicot	1,35	20	18,31	0,64
4.	Ketapang	<i>Terminalia catappa</i>	Dicot	1,38	20	19,73	0,66
5.	Sengon	<i>Albizia chinensis</i>	Dicot	1,43	20	13,16	0,41
6.	Acacia	<i>Acacia auriculiformis</i>	Dicot	1,27	20	18,74	0,74
7.	Glodokan	<i>Polyalthia longifolia</i>	Dicot	0,98	20	10,25	0,68
8.	Sawo kecil	<i>Manilkara kauki</i>	Dicot	0,79	20	10,39	1,06
9.	Kiarapayung	<i>Felicium decipiens</i>	Dicot	1,21	20	22,53	0,98
10.	Jackfruit	<i>Artocarpus heterophyllus</i>	Dicot	1,47	20	21,03	0,62
11.	Mango	<i>Mangifera indica</i>	Dicot	1,12	20	13,79	0,68
12.	Bintaro	<i>Cerbera manghas</i>	Dicot	1,07	20	7,55	0,40

Source: Analysis results, 2020

**Table 8.** Tree Biomass in the Urban Forest at Rajekwesi Type A Terminal

No.	Tree Name		Monocot/ Dicot	Tree Biomass ( $kg/\text{tree}$ )	Tree Age (year)	Tree Biomass per Year ( $kg/\text{year}$ )
	Local Name	Botanical name				
1.	Tanjung	<i>Mimusops elengi</i>	Dicot	10.066,492	6-8	1.646,370
2.	Mahogany	<i>Swietenia mahagoni</i>	Dicot	12.403,758	6-14	1.706,114
3.	Trembesi	<i>Samanea saman</i>	Dicot	54.436,134	6-17	3.245,903
4.	Ketapang	<i>Terminalia catappa</i>	Dicot	156,309	2-8	20,217
5.	Sengon	<i>Albizia chinensis</i>	Dicot	3.537,730	6-17	264,034
6.	Acacia	<i>Acacia auriculiformis</i>	Dicot	8.627,777	17	507,516
7.	Glodokan	<i>Polyalthia longifolia</i>	Dicot	7.416,387	6-12	1.092,508
8.	Sawo kecil	<i>Manilkara kauki</i>	Dicot	5.651,651	6	941,942
9.	Kiarapayung	<i>Felicium decipiens</i>	Dicot	550,570	6-15	38,927
10.	Jackfruit	<i>Artocarpus heterophyllus</i>	Dicot	51,527	6	8,588
11.	Mango	<i>Mangifera indica</i>	Dicot	89,635	6	14,939
12.	Bintaro	<i>Cerbera manghas</i>	Dicot	26,243	6	4,374
			Total ( $kg/\text{year}$ )			9.491,430

Source: Analysis results, 2020

### 3.3. Comparison between $CO_2$ Emission with the Trees Capacity to Absorb $CO_2$

The total  $CO_2$  emission of motor vehicles in Rajekwesi Type A Terminal was 292.058,087  $kgCO_2/\text{year}$ , while the amount of  $CO_2$  absorbed by trees in the terminal's urban forest was 16.023,44

$kgCO_2/\text{year}$ . If the amount of  $CO_2$  absorbed by the trees was compared to the amount of  $CO_2$  emission from the motor vehicles, the absorption capacity for  $CO_2$  was still much smaller than the emission rate. The percentage of  $CO_2$  balance in Rajekwesi Type A Terminal can be seen in Table 9.

**Table 9.**  $CO_2$  Balance at Rajekwesi Type A Terminal

No.	CO <sub>2</sub> Balance Component	Motor Vehicle Type	Total (kgCO <sub>2</sub> / year)	Percentage (%)
1.	CO <sub>2</sub> Emission	Small	10,429	0,004
		Motor cycle	6.842,446	2,343
		Big	874,175	0,299
		Sedan/ jeep	132,339	0,045
		Family car/ MPV	422,357	0,145
		Pick-up	153,300	0,052
		Microbus	13.914,530	4,764
		Bus	269.708,511	92,348
		Total	292.058,087	100
2.	CO <sub>2</sub> Sequestration	Trees and seedlings	16.023,440	5,486
3.	CO <sub>2</sub> Emission not absorbed by trees		276.034,650	94,514

Source: Analysis results, 2020

From Table 9, it can be learnt that the trees in the urban forest at Rajekwesi Type A Terminal could only absorb 16.023,44  $kgCO_2/\text{year}$  (5,486%) of the total motor vehicle  $CO_2$  emissions of 292.058,087  $kgCO_2/\text{year}$ .

Therefore, the function of the terminal urban forest as an absorber of  $CO_2$  emission is still not optimal.

#### 4. Conclusion

Based on the results of the research and discussion that have been carried out, several conclusions are obtained. First, when compared to other days, the highest CO<sub>2</sub> emission of motor vehicles at Type A Rajekwesi Terminal was on Saturdays (weekends) and it amounted to 826,870 kgCO<sub>2</sub>, of which 92,17 % was from bus emission (762,144 kgCO<sub>2</sub>).

Second, the amount of CO<sub>2</sub> absorbed by the trees in the urban forest at Rajekwesi Type A Terminal was 16.023,44 kgCO<sub>2</sub>/year, where the tree with the highest biomass was Trembesi (*Samanea saman*), which had 54.436,134 kg/tree.

Third, if the amount of CO<sub>2</sub> absorbed by trees (16.023,440 kgCO<sub>2</sub>/year) was compared to the total CO<sub>2</sub> emissions of motor vehicles (292.058,087 kgCO<sub>2</sub>/year), the CO<sub>2</sub> absorption was still smaller than the emission rate. Therefore, the function of the terminal urban forest as an absorber of CO<sub>2</sub> emission was still not optimal.

#### REFERENCES

- Anonymous. 2012. Jejak Karbon dan Kenaikan Emisi Gas Rumah Kaca. Institute for Essential Services reform (IESR) Indonesia: Jakarta.
- Anonymous. 2017. Ringkasan Eksekutif - Informasi Kinerja Pengelolaan Lingkungan Hidup Daerah (IKPLHD) Provinsi Jawa Timur Tahun 2016. Surabaya, Dinas Lingkungan Hidup Provinsi Jawa Timur. Hal. 9.
- Fandeli, C., Kaharuddin, dan Mukhlison. 2004. Perhutanan Kota, Fakultas Kehutanan. Universitas Gadjah Mada: Yogyakarta. Hal. 5, 10, 17, 30, 31, 39, 42, 48, 93, 126, 127, 135, 142, 153.
- Fandeli, C., dan Muhammad. 2009. Prinsip-Prinsip Dasar Mengkonservasi Lanskap. Gadjah Mada University Press: Yogyakarta. Hal. 154, 168, 177.
- Fitrada, W., Handika, R.A., dan Rodhiyah, Z. 2020. Potensi Vegetasi Hutan Kota Dalam Reduksi Emisi Karbondioksida (CO<sub>2</sub>) di Kota Jambi. Biospecies, Vol. 13 No. 1. Hal. 23-28.
- Hairiah, K., dan Rahayu, S. 2007. Petunjuk Praktis Pengukuran Karbon Tersimpan di Berbagai Macam Penggunaan Lahan, World Agroforestry Centre - ICRAF, SEA Regional Office. University of Brawijaya, UNIBRAW, Indonesia, Bogor. Pages. 17, 19, 28, 29, 30, 47.
- Hamdaningsih, S.S., Fandeli, C., dan Baiquni, M. 2010. Studi Kebutuhan Hutan Kota Berdasarkan Kemampuan Vegetasi Dalam Penyerapan Karbon di Kota Mataram, Majalah Geografi Indonesia, Vol. 24 No. 1. Hal. 1-9.
- Ihsan, M., Batubara, U.M., dan Susilawati, I.O. 2015. Biomassa di Atas Permukaan Tanah Pada Pohon dan Sapling di Ruang Terbuka Hijau Muhammad Sabki Propinsi Jambi. Prosiding Semirata 2015 Bidang MIPA BKS-PTN Barat Universitas Tanjungpura Pontianak. Hal. 343-350.
- Kosegeran, V.V., Kendekallo, E., Sompie, S.R.U.A., dan Bahrin. 2013. Perancangan Alat Ukur Kadar Karbon Monoksida (CO), Karbon Dioksida (CO<sub>2</sub>) dan Hidro Karbon (HC) Pada Gas Buang Kendaraan Bermotor, e-Journal Teknik Elektro dan Komputer.
- Ludang, Y., Alpian, dan Junaedi, A. 2017. Metode Pengukuran Serapan Karbondioksida Pada Pertumbuhan Anaka. Jurnal Pengelolaan Lingkungan Berkelanjutan, Vol. 1 No. 3. Hal. 1-6.
- Saadah, N. 2002. Gangguan Kenyamanan Lingkungan Beberapa Terminal di DIY Oleh Tingkat Pencemaran Karbondioksida dan Hubungannya dengan Kenaikan Suhu, Tesis. Universitas Gadjah Mada: Yogyakarta.
- Soedomo, M. 2001. Kumpulan Karya Ilmiah Mengenai Pencemaran Udara. Penerbit ITB: Bandung, Hal. 21, 24, 129, 228.
- Tim Penulis Pedoman Penyelenggaraan Inventarisasi GRK Nasional. 2012. Pedoman Penyelenggaraan Inventarisasi Gas Rumah Kaca Nasional, Buku II - Volume 1 Metodologi Penghitungan Tingkat Emisi Gas Rumah Kaca, Kegiatan Pengadaan dan Penggunaan Energi. Kementerian Lingkungan Hidup: Jakarta. Hal. 189-203.

# The Effectiveness of Urban Forest in Absorbing CO2 Emission at Rajekwesi Type A Terminal

## ORIGINALITY REPORT

6%

SIMILARITY INDEX

3%

INTERNET SOURCES

4%

PUBLICATIONS

1%

STUDENT PAPERS

## PRIMARY SOURCES

- |   |  |     |
|---|--|-----|
| 1 | Fan, Jia Feng, Hao Xu, Juan Yuan, and Bang Zhu Zhu. "Cluster Analysis of Industrial Transfer Park Based on Carbon Emission Intensity", Applied Mechanics and Materials, 2013.<br>Publication | 1%  |
| 2 | core.ac.uk<br>Internet Source  | 1%  |
| 3 | Moch. Samsul Arifin. "Above Carbon Stoks Potential in Universitas Negeri Semarang", E3S Web of Conferences, 2018<br>Publication  | 1%  |
| 4 | mafiadoc.com<br>Internet Source  | 1%  |
| 5 | www.dlmd.bravehost.com<br>Internet Source  | <1% |
| 6 | D A P Sari, D Fadiilah, A Azizi, Pawenary. "Energy Sector CO Emission In Palm Oil Mill ", Journal of Physics: Conference Series, 2019<br>Publication   | <1% |

7	<a href="https://onlinelibrary.wiley.com">onlinelibrary.wiley.com</a> Internet Source	<1 %
8	<a href="https://www.researchgate.net">www.researchgate.net</a> Internet Source	<1 %
9	<a href="https://jatimprov.go.id">jatimprov.go.id</a> Internet Source	<1 %
10	Reynolds, Steven D., and John H. Seinfeld. "Interim evaluation of strategies for meeting ambient air quality standard for photochemical oxidant", Environmental Science & Technology, 1975. Publication	<1 %
11	<a href="https://auf.isa-arbor.com">auf.isa-arbor.com</a> Internet Source	<1 %
12	Maurits Walalayo, Anik Vega Vitianingsih, Anastasia Lidya Maukar, Erri Wahyu Puspitarini, Fitri Marissa. "WEB-GIS KESESUAIAN LAHAN UNTUK PENGEMBANGAN HUTAN KOTA MENGGUNAKAN METODE MULTI-CRITERIA DECISION MAKING", Rabbit : Jurnal Teknologi dan Sistem Informasi Univrab, 2021 Publication	<1 %
13	A Kusumoarto, A Ernawati. " Ecological Carrying Capacity Analysis of Ecotourism Objects in II Resort Area, National Park ", IOP	<1 %

# Conference Series: Earth and Environmental Science, 2018

Publication

14

idoc.pub

Internet Source

<1 %

15

Junghwan Lee, Gwangyu Lee, Joonsoon Kim.

"Calculating total urban forest volume considering the carbon cycle in an urban area – focusing on the city of Chuncheon in South Korea.", Forest Science and Technology, 2014

Publication

<1 %

Exclude quotes Off

Exclude matches Off

Exclude bibliography On